

OFFICIAL

HOGAN & HARTSON L.L.P.

500 SOUTH GRAND AVENUE
SUITE 1900
LOS ANGELES, CA 90071Tel.: (213) 337-6700
Fax: (213) 337-6701RECEIVED
CENTRAL FAX CENTER

FEB 19 2004

IMPORTANT NOTICE
TELECOPY/FACSIMILE COVER LETTERWASHINGTON, DC
BRUSSELS
BUDAPEST*
LONDON
MOSCOW
PARIS*
PRAGUE*
TOKYO
WARSAW
BALTIMORE, MD
BOULDER, CO
COLORADO SPRINGS, CO
DENVER, CO
IRVINE, CA
MCLEAN, VA
MIAMI, FL
NEW YORK, NY (PARK AVE)
NEW YORK, NY (THIRD AVE)
ROCKVILLE, MD

*Affiliated Office

TO: U.S. Patent and Trademark Office

Examiner: Benny T. Lee
Art Unit: 2817

DATE: February 13, 2004

FROM: Barry Shuman

TIME:

TOTAL NO. OF PAGES, INCLUDING COVER: 3

The attached information is **CONFIDENTIAL** and is intended only for the use of the addressee(s) named above. If the reader of this message is not the intended recipient(s) or the employee or agent responsible for delivering the message to the intended recipient(s), please note that any dissemination, distribution or copying of this communication is strictly prohibited. Anyone who receives this communication in error should notify us immediately by telephone and return the original message to us at the above address via the U.S. Mail.

MESSAGE:

RE: U.S. Patent Application Serial No.: 09/709,098; Our Ref. 81707.0164

I hereby certify that the following documents:

- Letter/Abstract of DE4208058

are being facsimile transmitted to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, for filing in the above application.

February 13, 2004
Date of Deposit
Diane Zynn

TELECOPY/FAX NUMBER: 703-872-9319

CLIENT NUMBER: 81707.0164

ATTORNEY BILLING NUMBER: 1966

CONFIRMATION NUMBER: 571-272-1764 (please return fax to Diane Zynn)

FEB 19 2004

Appl. No. 09/709,098

OFFICIAL

Attorney Docket No. 81707.0164
Customer No. 26021

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Naoyuki SHINO, *et al.*

Serial No: 09/709,098

Filed: November 10, 2000

For: WIRING BOARD

Art Unit: 2817

Examiner: Benny T. Lee

I hereby certify that this correspondence is
being transmitted via facsimile to
(703) 872-9319:
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450 on

February 13, 2004

Date of Deposit

Diane Zynn

Name

Signature

02/13/04
Date

Mail Stop AF

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Dear Sir:

Per our telephone conversation of February 13, 2004, I am attaching an Abstract, which serves as a confirmation that DE4208058 is a valid number. Also, it would be greatly appreciated if the Examiner could enter DE4208058 on form PTO-892.


If there are any fees due in connection with the filing of this response, please charge the fees to our Deposit Account No. 50-1314.

Respectfully submitted,

HOGAN & HARTSON L.L.P.

Date: February 13, 2004

By:


Barry M. Shuman

Registration No. 50,220


Attorney for Applicant(s)

500 South Grand Avenue, Suite 1900
Los Angeles, California 90071
Phone: 213-337-6700
Fax: 213-337-6701

Waveguide to microstrip transition for micro and millimetre range - has planar substrate with microstrip line and coupling slot t waveguide formed on separate planar layer.

Patent number: DE4208058
Publication date: 1993-09-16
Inventor: MENZEL WOLFGANG PROF DR ING (DE);
GRABHERR WILFRIED DIPL ING (DE)
Applicant: DEUTSCHE AEROSPACE (DE)
Classification:
- International: H01P5/107
- european: H01P5/107
Application number: DE19924208058 19920313
Priority number(s): DE19924208058 19920313; DE19934329570 19930902

Also published as:

 DE4329570 (A1)

Abstract of DE4208058

The waveguide to microstrip transition has a planar substrate (1) with a microstrip line (2). Beneath this line there is a coupling slot (3), at a quarter wavelength from the end (20), in the ground surface (7). On the back surface there is a rectangular waveguide (6) with a second planar substrate (5) having a dipole element (4) on its surface.

The boundary contour (30) of the coupling slot is rectangular with sides (140) parallel to the waveguide. High frequency power is coupled between the microstrip, the coupling slot and the dipole in the waveguide.

ADVANTAGE - Simple construction.

Data supplied from the esp@cenet database - Worldwide